



# The multiGuard® product series

ADVANCED GSM UNITS FOR  
MANAGEMENT, CONTROL AND ALARM

Monitor your installations with GSM  
independent of internet and land-lines

From the simple solution in your private home  
to the large, complex industrial installation –  
the multiGuard® units from Profort  
are designed to suit every need

The multiGuard® series includes 12 different  
GSM units

See all units and specifications on the back of this brochure



DEVELOPED AND PRODUCED IN DENMARK

**FREE web interface and apps** – SPECIALLY DEVELOPED FOR multiGuard®  
units.

**masterView®** setup is a free online platform for setup, control and  
monitoring of Profort GSM units.

**masterView®** can also be used to monitor units controlling e.g. street lights,  
pumps, wells, irrigation, cooler/freezer, as well as all kinds of alarm systems.

With the Profort **myHome®** app you can control heat pumps and monitor  
e.g. your vacation home with a mobile phone.

The user has complete control – via the internet.

masterView® and myHome® can be used on PC/Mac, tablet and smartphone



# The multiGuard® series

## SPECIFICATIONS



	myHome	myHome Alarm	Remote IO	Remote LAN	Technic IO	Technic RF
Profort number	006820	009310	009320	009510	009330	009340
GSM network	2G	2G	2G	-	2G	2G
Output relay	-	-	1	1	2	2
Inputs digital	-	-	3	3	3	3
Inputs analog	-	-	1	1	2	2
Infrared transmission	2 built-in + 1 external	2 built-in + 1 external	2 built-in + 1 external	2 built-in + 1 external	-	-
Box	Small design box, white	Design box, white	Design box, grey	Design box, grey	Design box, black	Design box, black
Power supply	5V power supply incl.	12V power supply incl.	12V power supply incl.	5V power supply incl.	12V power supply incl.	12V power supply incl.
Back-up battery	3,6V lith. incl.	3,6V lith. incl.	3,6V lith. incl.	-	3,6V lith. incl.	3,6V lith. incl.
Alarm as	Text message	Text message/DTMF/Email	Text message/DTMF/Email	Email	Text message/DTMF/Email	Text message/DTMF/Email
Module wireless	-	-	-	-	-	yes
Display	-	-	-	-	-	-
RS232 connection	-	-	yes	yes	yes	yes
Modbus	-	-	-	-	-	-
Ethernet interface	-	-	-	yes	-	-
Temp/humidity probe	Both built-in	Both built-in	Both built-in	Temperature built-in	Add on	Add on



	DIN4	DIN6	DIN9	Master IO	Master RF	Piccolo Light
Profort number	009012	007930	007940	004970	004975	004965
GSM network	2G	2G and 3G	2G and 3G	2G and 3G	2G and 3G	2G and 3G
Output relay	1	2	4	8	8	8
Inputs digital	3	4	8	8	8	8
Inputs analog	1	1	2	4	4	4
Infrared transmission	-	1 external	-	-	-	-
Box	4-module DIN	6-module DIN	9-module DIN	IP65	IP65	IP65
Power supply	12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC
Back-up battery	3,6V Lith./acquisition	9V accu/acquisition	9V accu acquisition	9V accu acquisition	9V accu acquisition	9V accu acquisition
Alarm as	Text message/DTMF/Email	Text message/DTMF/Email	and 90 secs. voice	Text message/DTMF/Email	Text message/DTMF/Email	Text message/DTMF/Email
Module wireless signal	-	-	-	Add on	Yes	Yes
Display	-	-	-	Add on	Yes	Yes
RS232 connection	Yes	Yes	Yes	Yes	Yes	Yes
Modbus	-	Yes	Yes	Yes	Yes	Yes
Ethernet interface	-	-	-	Yes	Yes	Yes
Temp/humidity probe	-	-	-	-	Via wireless	Via wireless

