



The multiGuard[®] product series

ADVANCED GSM UNITS FOR
MANAGEMENT, CONTROL AND ALARM

Monitor your installations with GSM
independent of internet and phone lines

From a home alarm system to a private security system
to an industrial installation –
the multiGuard[®] is the perfect solution for Profort
alarm systems and home automation.

The multiGuard[®] series is available in 12 different
GSM models

Each model is specifically designed for your application

89 9@CD98 5B8 DFC81 798 B 89BA 5F?

• **Web interface** and **apps** – 24/7 access to multiGuard[®]
control panel

masterView[®] setup and control online platform for
Profort GSM units

masterView[®] also offers a range of control options
for your multiGuard[®] units via a range of
Profort mobile apps including the myHome[®] app
for home automation and the myAlarm[®] app
for alarm systems.

Control your multiGuard[®] units – via the internet

• **Control your multiGuard[®] units via the internet**



HY'a ulTiGuard® serieg

SPECIFITATIONS



	myHome	myHome Alarm	Remote IO	Remote LAN	Technic IO	Technic RF
Profort number	006820	009310	009320	009510	009330	009340
GSM network	2G	2G	2G	-	2G	2G
Output relay	-	-	1	1	2	2
Inputs digital	-	-	3	3	3	3
Inputs analog	-	-	1	1	2	2
Infrared transmission	2 built-in + 1 external	2 built-in + 1 external	2 built-in + 1 external	2 built-in + 1 external	-	-
Box	Small design box, white	Design box, white	Design box, grey	Design box, grey	Design box, black	Design box, black
Power supply	5V power supply incl.	12V power supply incl.	12V power supply incl.	5V power supply incl.	12V power supply incl.	12V power supply incl.
Back-up battery	3,6V lith. incl.	3,6V lith. incl.	3,6V lith. incl.	-	3,6V lith. incl.	3,6V lith. incl.
Alarm as	Text message	Text message/DTMF/Email	Text message/DTMF/Email	Email	Text message/DTMF/Email	Text message/DTMF/Email
Module wireless	-	-	-	-	-	yes
Display	-	-	-	-	-	-
RS232 connection	-	-	yes	yes	yes	yes
Modbus	-	-	-	-	-	-
Ethernet interface	-	-	-	yes	-	-
Temp/humidity probe	Both built-in	Both built-in	Both built-in	Temperature built-in	Add on	Add on



	DIN4	DIN6	DIN9	Master IO	Master RF	Piccolo Light
Profort number	009012	007930	007940	004970	004975	004965
GSM network	2G	2G and 3G	2G and 3G	2G and 3G	2G and 3G	2G and 3G
Output relay	1	2	4	8	8	8
Inputs digital	3	4	8	8	8	8
Inputs analog	1	1	2	4	4	4
Infrared transmission	-	1 external	-	-	-	-
Box	4-module DIN	6-module DIN	9-module DIN	IP65	IP65	IP65
Power supply	12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC	230 VAC 12-24V AC/DC
Back-up battery	3,6V Lith./acquisition	9V accu/acquisition	9V accu acquisition	9V accu acquisition	9V accu acquisition	9V accu acquisition
Alarm as	Text message/DTMF/Email	Text message/DTMF/Email	and 90 secs. voice	Text message/DTMF/Email	Text message/DTMF/Email	Text message/DTMF/Email
Module wireless signal	-	-	-	Add on	Yes	Yes
Display	-	-	-	Add on	Yes	Yes
RS232 connection	Yes	Yes	Yes	Yes	Yes	Yes
Modbus	-	Yes	Yes	Yes	Yes	Yes
Ethernet interface	-	-	-	Yes	Yes	Yes
Temp/humidity probe	-	-	-	-	Via wireless	Via wireless

